

Features and Benefits

- Economical, all-purpose ceiling tile pattern in various sizes.
- Optional FIRECODE™ formulation designed to meet life safety codes.

Applications

















- Administrative offices
- Corridors
- Mass merchandisers
- Convenience stores

Fissured

Acoustical Ceilings

Technical Service 800 USG.4YOU
 Web Site www.usg.com
 Samples/Literature 888 874.2450
 Samples/Literature Fax 888 874.2348
 Customer Service 800 950.3839
 Literature Number SC1815

 UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost																
Fissured Panels  	2' x2' x5/8"	Class A	560	.55	33	.82	White	A, B, C	26%	\$																
	2' x2' x5/8"		585	.55	35	.82	White	A	46%	\$																
	2' x4' x5/8"	Class A	562	.55	35	.82	White	A, B	26%	\$																
	2' x4' x5/8"		586	.55	35	.82	White	A	46%	\$																
	2' x2' x5/8"	Class A	506	.55	33	.82	White	D	26%	\$																
	2' x4' x5/8"	Class A	507	.55	35	.82	White	D	26%	\$																
<table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> <tr> <th>DONN® DX®/ DXL™</th> <th>DONN DXW™</th> <th>CENTRICITEE™</th> <th>DONN DX/DXL</th> </tr> </thead> <tbody> <tr> <td colspan="4">Grid Profile Options</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>											A	B	C	D	DONN® DX®/ DXL™	DONN DXW™	CENTRICITEE™	DONN DX/DXL	Grid Profile Options							
A	B	C	D																							
DONN® DX®/ DXL™	DONN DXW™	CENTRICITEE™	DONN DX/DXL																							
Grid Profile Options																										
																										

ASTM E1264 classification

Type III, Form 2, Pattern CD

ASTM E84 surface burning characteristics

Class A

Flame spread: 25

Smoke developed: 10

Weight

.65-.98 lb./ft.² (Class A)

1.14-1.22 lb./ft.² (FIRECODE™)

Thermal resistance

R-1.3

Maximum backloading

See Warranty for details.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Footnotes

1. LR values are shown as averages.

2. For details, see the Recycled Content selector.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
 USG Interiors, Inc.
 125 South Franklin Street
 Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:
 CENTRICITEE, DONN, DX, DXL, DXW, FIRECODE, USG.

SC1815/rev. 6-04
 © 2004, USG Interiors, Inc.
 Printed in U.S.A.