














Features and Benefits



- Fine textured cast product with durable surface that resists scrapes caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches to enhance lifelong panel appearance.
- Optional FIRECODE™ formulation designed to meet life safety codes.
- Nearly two times more impact resistant than typical fine textured ceiling panels. (ASTM C367 – 2" ball hardness test).






Applications

- Conference and lobby areas
- Entertainment and gaming
- Executive offices
- Hotels and restaurants
- Retail stores
- Education environments
- Transportation terminals

 UL Classified

	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Cost
Frost™ Panels	(SLB) 	2' x2' x3/4"	Class A	440	.70 	40 	.82	White	A	67%	\$\$
		2' x2' x3/4"		415	.55 	35 	.82	White	A	67%	\$\$
		2' x4' x3/4"	Class A	450	.70 	38 	.82	White	A	67%	\$\$
	(FL) 	2' x4' x3/4"	Class A	460	.70 	38 	.82	White	B, C, D	67%	\$\$
Frost Pedestals I Panels Triple-step scoring	(PE/IL) 	2' x2' x3/4"	Class A	400	.70 	35	.82	White	E	67%	\$\$\$

Pedestals I	RENDITIONS™³
	

Patterns	A DONN® DX®/ DXL™	B CENTRICITEE™	C FINELINE® 1/8	D FINELINE	E CENTRICITEE
Grid Profile Options					

ASTM E1264 classification
 Type III, Form 4, Pattern E
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 15
Weight
 1.55 lb./ft.²
 1.60 lb./ft.² (Pedestals)

Thermal resistance
 R-1.6 (Class A)
 R-1.1 (FIRECODE™)
Maximum backloading
 See Warranty for details.
Maintenance
 Can be cleaned easily with a soft brush or vacuum.
Impact resistance
 ASTM C369 – tested to min. 190 lbf. for 1/4" depression by a 2" steel ball.

Texture
 The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production date code.

Footnotes
 1. LR values are shown as averages.
 2. For details, see the Recycled Content selector.
 3. See RENDITIONS Face-Routed Ceiling Panels (IC327) in USG Specialty Ceilings binder for more information.

SAFETY FIRST!
 Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.