



Premier Hi-Lite™ *ClimaPlus™*



Medium textured panel, Twill perforated and unperforated



Medium textured panel, Kapok perforated and unperforated



Features and Benefits

- Washable vinyl face for easy maintenance.
- Excellent noise reduction with NRC of .60 or .75 for greater sound control in open-plan spaces.
- *CLIMAPLUS™* 15-year System Warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with USG's *DONN®* Brand Suspension Systems.
- Lightweight fiberglass basemat makes installation fast and easy.

Applications

- Discount stores
- Grocery stores
- Mass merchandisers
- Retail stores

Premier Hi-Lite™ ClimaPlus™

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC1838



UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color ²	Grid Options	Recycled Content ³	Panel Cost
(SQ) 	2' x2' x5/8"	Class A	7050G Perf.	.75 	20	.76	White	A, B, C, D	29%	\$
	2' x2' x5/8"	Class A	7052G Unperf.	.60	20	.76	White	A, B, C, D	29%	\$
	2' x4' x5/8"	Class A	7051G Perf.	.75 	20	.76	White	A, B, C, D	29%	\$
	2' x4' x5/8"	Class A	7053G Unperf.	.60	20	.76	White	A, B, C, D	29%	\$
(SQ) 	2' x2' x5/8"	Class A	7054G Perf.	.75 	20	.76	White and Black	A, B, C, D	29%	\$
	2' x2' x5/8"	Class A	7056G Unperf.	.60	20	.76	White	A, B, C, D	29%	\$
	2' x4' x5/8"	Class A	7055G Perf.	.75 	20	.76	White and Black	A, B, C, D	29%	\$
	2' x4' x5/8"	Class A	7057G Unperf.	.60	20	.76	White	A, B, C, D	29%	\$
A DONN® DX®/ DXL™		B DONN DXW™		C ZXLA™		D AX™				
Grid Profile Options										

ASTM E1264 classification
Type XII, Form 1, Pattern CE
(Perforated), Pattern E
(Unperforated)

ASTM E84 surface burning characteristics
Class A

Flame spread: 25
Smoke developed: 50

Weight
0.143 lb./ft.²
Thermal resistance
R-2.7

Maximum backloading
See Warranty for details.
Maintenance
Can be cleaned easily with a damp sponge.

Footnotes
1. LR values are shown as averages.
2. See color selectors for more information.
3. For details, see the Recycled Content selector.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company: AX, CLIMAPLUS, DONN, DX, DXL, DXW, PREMIER HI-LITE, USG, ZXLA.

SC1838/rev. 6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.