



**Features and Benefits**

- Simple lay-in design provides 100% access.
- ACOUSTIBOND™ sound backer produces .65 NRC without additional acoustical material when panels are installed within an enclosed plenum (minimum plenum depth 18”).
- Aluminum panels are easy to clean and durable.
- Available in numerous perforation patterns in painted, anodized, DIAMONDFLEX™ and natural metals.
- Uniquely designed trim provides reveal edge on field-cut panel.
- Available with same edge details as USG acoustical panels.




**Applications**







- Computer and utility rooms
- Entertainment
- Gaming
- Frequently accessed plenums

PANZ™ Metal Ceiling Panels (FL edge) in Flat White/DONN® Brand CENTRICITEE™ Suspension System

<b>Product Information</b>	<b>Materials</b>	Panels: Aluminum.		
	<b>Finishes</b>	Anodized finishes, DIAMONDFLEX™ and smooth or perforated panels in Standard Colors, Advantage Colors and custom colors. See Metal Finishes and Metal Perforations selectors for more finish options.		
	<b>Typical Sizes</b>	2' x 2'	2' x 4'	1' x 4'

Acoustics¹	Description	Optional Acoustical Material	Sound Rating – NRC	
			Perforation A062	Perforation A116
	Perforated panel	ACOUSTIBOND® backer	.65	.70
Perforated panel	1-1/2", 6 lb. density fiberglass	.90	.95	
Perforated panel	2" .75 lb. fiberglass in poly bag	.85	.90	

Panels	Smooth Panel	Perforated Panel	Perforated Panel with ACOUSTIBOND®
			

Edge Details	Square Edge with 15/16" DONN® Brand DX®/DXL™ Suspension	Square Edge with 9/16" DONN Brand CENTRICITEE™ (DXT) Suspension	Shadowline Edge with 15/16" DONN Brand DX®/DXL™ Suspension	FINELINE Edge with 9/16" DONN Brand CENTRICITEE™ Suspension
				
	FineLine Edge with 9/16" FINELINE® (DXF) Suspension	FineLine Edge with 9/16" FINELINE 1/8 (DXFF) Suspension		
				

**Supporting technical literature**  
IC33104  
**Light reflectance**  
Flat White: LR-0.8 (less with perforations).

**Recycled content**  
Contact Technical Services at 800 USG.4YOU.  
**Footnote**  
1. Based on A062 perforation.  
2. ACOUSTIBOND backer not standard with DIAMONDFLEX panels.

**SAFETY FIRST!**  
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.