










Features and Benefits

- Metal, woven lay-in panels with powder-coated finish are abuse resistant and highly durable.
- Four cell sizes offer flexibility to meet design and budget needs.
- Combine with the GRIDWARE™ Suspension System to create custom ceiling system.
- Easy installation into standard DONN® Brand Suspension Systems.
- Easily accommodates lightweight signage.
- Available in High-Gloss White, Advantage Colors, Chrome, and custom colors.

Applications

- Accent areas
- Educational
- Health care
- Retail stores

Product Information	Materials	Robotically welded steel wire.
	Finishes	High-Gloss White, Advantage Colors, Chrome, and custom colors .
	Typical Size	2' x 2'
	Wire Thickness	Panels are 1/8"; Forms are 3/16"

WireWorks Ceiling Panels 2' x 2' 1/8" Wire	1" x 1" wire spacing 	2" x 2" wire spacing 	3" x 3" wire spacing 	4" x 4" wire spacing 
	WireWorks Forms 2' x 2' 3/16" Wire	Weave 	Ripple 	Small Wave 

Supporting technical literature
IC34103
Recycled content
Contact Technical Services at 800-USG-4YOU.
Metric equivalents
Contact Technical Service for additional information.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.